

ROTATING SIEVE

- Suitable for a wide variety of materials
- Sieve drum dia. 400 mm, length 900 mm (RS400) / 800 mm (RS350)
- Drum can be set at various angles
- Sieve mesh diameter 20 mm
- Standard sieve insert with a mesh size of 10 mm
- Sieve drum speed 42 rpm
- Throughput depending on material 3 m³/h



Sieve drum
dia. 400 mm

Drum can be
set at various
angles

Wheels



The sieved top soil is ideal for new beds,
and for refining and loosening up firm,
older soil.



The standard brush strip ensures
reliable cleaning of the screening drum,
especially when using damp material.



Thanks to the sieve drum design,
nothing is in the way when feeding it.



By selecting the drum angle, you can
control the speed of the material
passing through.



Thanks to the standard wheels and the
light weight of 37 kg, the rotary sieve is
mobile and can be used in every corner of
your garden.



SPECIFICATIONS

	RS350	RS400
Dimensions L x W x H	1040 x 665 x 1480 mm	1080 x 740 x 1400 mm
Throughput (depending on material)	3 m³/h	3 m³/h
Sieve drum Ø	400 mm	400 mm
Sieve drum length	800 mm	900 mm
Drum inclination	3 stages	10° / 2 stages
Sieve drum speed	42 rpm	42 rpm
Sieve opening Ø	20 mm	20 mm
Sieve insert with mesh (size)	10 mm	10 mm
Motor	230 – 240 V~ / 50 Hz	230 – 240 V~ / 50 Hz
Motor Output	250 W	360 W

LOGISTICAL DATA

	RS350	RS400
Weight net / gross	32 / 37 kg	37 / 44 kg
Packaging dimensions	890 x 580 x 940 mm	1040 x 480 x 780 mm
Article number	1904501901	42030000
Barcode	4014915089186	4014915010975
20 Container	44 pcs	48 pcs
40 Container	96 pcs	104 pcs
40 HQ Container	130 pcs	144 pcs